

DEESA

Lightweight and powerful, the Stanley CO25 Cutoff Saw is ideal for cutting concrete, masonry, pipe, structural steel beams and guardrail.

The CO25 multi-hand position cast aluminum handle with interlocking safety trigger provides ergonomic grip at a variety of tool angles for reduced operator fatigue.

Tamper-proof flow control meets ANSI specifications for speed control, reducing the risk of over-speeding the cutting wheel.

Cutoff saws can be used with readily available standard abrasive wheels and wet or dry diamond blades.

Internal blade brake retards spindle rotation upon release of trigger to greatly reduce wheel coast time.

Adjustable cast aluminum wheel guard is designed to provide excellent durability, allow cutting near obstructions and minimize tool weight. Available handle extension kit provides for upright operation to meet operator preference.



The Stanley saw cart with a CO25 makes the ideal tool combination for accurate dimensional cutting of concrete flat work.

Heavily weighted frame of the Stanley saw cart provides a stable platform for slab cutting. Handle-mounted control provides convenient adjustment of cutting depth.



SPECIFICATIONS

| ITEM | USA | METRIC |
|------------------|----------------------------|---------------|
| Output Capacity | 14 in. Wheel | 35.6 cm |
| Input Flow Range | 7 - 9 gpm | 26 - 34 lpm |
| Input Pressure | 1500 - 2000 psi | 105 - 140 bar |
| Optimum Flow | 8 gpm | 30 lpm |
| Weight | 20 lbs | 9.1 kg |
| Length | 21 in. | 53.3 cm |
| Width | 11 in. | 28 cm |
| Motor | HYREVZ™ Gear | |
| Porting | 8 SAE O-Ring | |
| Connector | 3/8 in. Male Pipe Hose End | |



DEF SA



March 2013

ORDERING INFORMATION

| Model No. | Description | |
|-----------|---|--|
| CO25141 | Cutoff Saw, Counter-Clockwise Rotation, 1 in. Arbor | |
| CO25541 | Cutoff Saw, Clockwise Rotation, 1 in. Arbor | |

Note: All above are open-center system.

ACCESSORIES

| Part No. | Description |
|----------|---|
| 02691 | 14 in. / 35.6 cm diameter, CO25 Metal Cutting Abrasive Wheel, 1 in. Arbor |
| 02692 | 14 in. / 35.6 cm diameter, CO25 Masonry Cutting Abrasive Wheel, 1 in. Arbor |
| 62358 | 14 in. / 35.6 cm diameter, CO25 Dry Cut Diamond Blade |
| 34175 | Handle Extension Kit |
| 33228 | Water Attachment |
| 69704 | Water Tank Kit for Saw Cart |
| 69290 | Saw Cart |

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specifications and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.