



**SPECIFICATIONS**

ITEM	CS25		CS28	
	U.S.A.	METRIC	U.S.A.	METRIC
Cut Capacity	13 in	33 cm	13 in	33 cm
Weight *	10.4 & 11 lb	4.7 & 5 kg	10.4 & 11 lb	4.7 & 5 kg
Overall Length **	75 & 90 in	190 & 230 cm	75 & 90 in	190 & 230 cm
Pressure	1000-2000 psi	70-140 bar	1000-2000 psi	70-140 bar
Flow Range	4-6 gpm	15-23 lpm	7-9 gpm	26-34 lpm
Optimum Flow	5 gpm	20 lpm	8 gpm	30 lpm
Porting	-8 SAE		-8 SAE	
Connect Size/Type	3/8 NPT Male Adapter		3/8 NPT Male Adapter	

\* Weight includes bar and chain but not quick couplers.

\*\* Length includes bar and chain but not quick couplers.

The CS25 and CS28 pole chain saws are ideal for use by right-of-way crews, utilities, parks departments and grounds-keepers. Lightweight, they feature fiberglass poles for convenient handling in tight spots and automatic chain oiling for long, reliable service.

The CS28 is designed for HTMA Type II circuits and has an optimum flow of 8 gpm/30 lpm. The CS25 is ideal for HTMA Type I circuits commonly found on bucket trucks where hydraulic circuit flow is often limited to 4-6 gpm /15-23 lpm.

For greater versatility, the Stanley "Dual Spool" permits the user to adjust the saw to operate from either open or closed-center circuits.

The CS25/CS28 use a low kickback, .325-pitch saw chain for added safety. The flow rating is easily changed by replacing the gear chamber and two gears.

**Model CS28 Pole Chain Saw**

Features	Benefits
Pole center line close to bar centerline	Reduced operator fatigue
External bar oiler	Quick/Convenient adjustments
Common bar and chain	Easy to source replacement parts
OC/CC dual spool	Match the tool hydraulics to the circuit
Integral branch hook	Extra long bucking face/brush management
Meets ASTM F711-83	Passes requirements for live-line tools
Rim Sprocket	Smoother operation, retains chain
Guide Plates	Keeps loose chain in place

**Safety Note:** The CS25 and CS28 trigger will not operate if the trigger guard is removed.

## ORDER INFORMATION

MODEL NO.	DESCRIPTION
CS25811	Long Reach 90"/230 cm, oc/cc, 4-6 gpm/15-23 lpm
CS2581101	Long Reach 90"/230 cm, oc/cc, 4-6 gpm/15-23 lpm, CE, includes FF couplers
CS25812	Short Reach 75"/190 cm, oc/cc, 4-6 gpm/15-23 lpm
CS28811	Long Reach 90"/230 cm, oc/cc, 7-9 gpm/26-34 lpm
CS2881101	Long Reach 90"/230 cm, oc/cc, 7-9 gpm/26-34 lpm, CE, includes FF couplers
CS28812	Short Reach 75"/190 cm, oc/cc, 7-9 gpm/26-34 lpm

## ACCESSORIES

PART NO.	DESCRIPTION
05144	Chain/Bar Guard
07616	Sprocket Spline Adapter
07629	Rim Sprocket 0.325 P
08347	13 in (33 cm) saw bar
08348	Saw Chain for 13 in (33 cm) bar
11464	Scrench
11294	Flat File
11298	Depth Gauge
12363	File guide with file

## WARRANTY

Stanley tools and associated parts are warranted against defects in materials and workmanship for a period of 12 months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum voltage and current ratings are exceeded.

All Stanley Hydraulic Tools, parts, accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your applications, please consult Stanley Hydraulic Tools.

**STANLEY**  
Hydraulic Tools

Visit our website at [www.stanley-hydraulic-tools.com](http://www.stanley-hydraulic-tools.com)

**I**NTERMOUNTAIN  
**S**ALES, INC.  
Utility Tools for Today!

**Stanley Hydraulic Tools**  
3810 S.E. Naef Road  
Milwaukie, Oregon 97267  
Tel 503•659•5660  
Fax 503•652•1780