

Specifications

Transmitter:

- **Output Frequency:** 82.175 kHz
- **Output Power:**
 - **Normal Setting:** 0.25 watt
 - **High Setting:** 1.0 watt
- **Conductive Tracing:**
 - **Normal Power:** 2 to 8,000 ohms (-6 dB)
 - **High Power:** 2 to 3,000 ohms (-6 dB)
- **Inductive Tracing:**
 - **Normal Power Magnetic Strength:** 15 Vm²
 - **High Power Magnetic Strength:** 25 Vm²
- **Battery Type:** Four D-cell batteries (included)
- **Battery Life:** Up to 130 hours with high-quality alkaline batteries
- **Weight (with batteries):** 4 lbs

Receiver:

- **Frequency:** 82.175 kHz
- **Operating Modes:**
 - **Standard Mode:** Automatic response
 - **Lateral Mode:** Programmable
- **Guidance Indicators:**
 - **Left/Right Guidance:** Audible and visual
 - **Azimuth Indicator:** Visual
 - **Over-Target Indicator:** Both visual and audible



- **Signal Measurements:**
 - **Signal Strength Indicator:** Numeric display with audible feedback
 - **Signal Current Measurement:** Numeric display, automatic
 - **Depth Measurement:** Numeric display, automatic
- **Battery Type:** Two D-cell batteries (included)
- **Battery Life:** 80 to 130 hours, depending on volume settings
- **Weight (with batteries):** 3.60 lbs

Environmental Ratings:

- **Ingress Protection Rating:** IP65 (water-resistant, withstands water jets)
- **Operating Temperature Range:** -4°F to 140°F (-20°C to 60°C)
- **Relative Humidity:** 0 to 95%, non-condensing

General Information:

- **Field Carry Weight (with accessories):** 15.5 lbs.
- **Shipping Weight:** 17.5 lbs.
- **Warranty:** 2-year limited warranty (terms and conditions may vary outside the U.S.)



**INTERMOUNTAIN
SALES, INC.**
Utility Tools for Today!

**3792 South Lipan Street
Englewood, Colorado 80110**

Telephone: (303) 762-1070 or 1-800-373-3212
FAX: (303) 762-0996 www.intermntsales.com