



FEATURES:

- The integral Stanley HyrevzTM gear motor is manufactured to exacting standards to deliver maximum efficiency.
- The over-sized motor run-down valve allows the motor to freely run down in speed when the grinder is turned off ensuring that a properly installed wheel will not spin off the spindle.
- The built-in reverse-check valve in the handle prevents operating the grinder when reverse-plumbed to the hydraulic system.
- The Stanley dual-spool selector is accessable under a seal plug at the rear of the tool.

SPECIFICATIONS

GR30	
Capacity	9 in. Wheel on 5/8- 11 thrd Arbor
Speed	5600 rpm at 8 gpm
	30 lpm
Input Flow	7-9 gpm
Range	26-34 lpm
Input Pressure	1000-2000 psi
	70-140 bar
Weight	12.5 lbs
	5.7 kg
Length	8.5 in.
	21.6 cm
Width	8.7 in
	22.1 cm
Height	17.5 in.
	44.5 cm
Motor	Stanley HyrevzTM
	Gear
Porting	-8 SAE 0-ring
Hose Whips	Yes, Includes
	Speed Limiter

OPEN-CENTER OR CLOSED-CENTER? YOU CHOOSE -THE POWER OF HYDRAULICS





ORDERING INFORMATION

MODEL	PART NO.	DESCRIPTION
GR30	GR30701	9-inch Grinder , OC/CC Selector
	GR3070101	9-inch Grinder, OC/CC Selector, CE
	GR30701S	Grinder OC/CC Dry RR 9" 5/8-11

ACCESSORIES

ITEM NO	DESCRIPTION
02587	Grinding wheel for Metal, 9-inch diameter x 5/8-11 Thread
02588	Grinding Wheel for Masonry, 9-inch Diameter x 5/8-11 Thread
03691	Grinding Wheel, 7-inch Diameter x 5/8-11 Thread
05194	Adapter, 5/8-11 Thread, Depressed Center Wheel



WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.