




















Transmitter Accessories and Signal Clamps

Direct Connection Leads and Accessories

Picture	Order Code	Description	Plug Type	1-Watt 5-Watt 10-Watt	25-Watt	VM-550FF VM-560FF	VM-810 VM-850 vScan
Direct Connection Lead, Standard Clips							
	2.205.01.00018	Direct Connection Lead with Standard Clips are for day to day use where the size of the targeted lines varies, and connections are to common services.		✓	-	✓	✓
	2.222.02.00007			-	✓	-	-
Direct Connection Lead with large clips							
	2.213.02.00013	Direct Connection Lead with large clips is suited for the gas and water industries where connections will be made to bell housings or fire hydrants.		✓	-	✓	✓
	2.219.02.00090			-	✓	-	-
Direct Connection Lead with Telco Clip							
	2.213.02.00007	Direct Connection Lead with Telco clips is suitable for telephone cable where the user cannot access the sheath of the cable.		✓	-	✓	✓
	2.219.02.00091			-	✓	-	-
Ground Extension Lead							
	2.200.04.00082	Ground Extensions - Use the extension leads to extend the ground connection to reach a suitable grounding position.	30 feet	✓	✓	✓	✓
	2.200.04.00081		98 feet	✓	✓	✓	✓
Clamp and Leads Adapter							
	2.219.02.00094	Adapter, 3 pin silver plug to Twist/Lock plug.	-	✓	-	✓	✓
Live Cable Connector							
	1.204.10.00001	Live Cable Connector is usable on live cables up to 480 V ac 60/50Hz. The Live Cable Connector operates on frequencies of 8kHz, 33kHz and SIS.		✓	-	✓	✓
	1.204.10.00002			-	✓	-	-
Live Plug Connector							
	1.204.07.00002	Live Plug Connector is used to safely inject a locate frequency onto a live street distribution cable using a standard household mains socket from a building.		✓	-	✓	✓
	1.204.07.00005			-	✓	-	-





3 Pin Silver Plug



Twist/Lock plug

Transmitter Clamps

Picture	Order Code	Description	Plug Type	5-Watt 10-Watt SiS	25-Watt	VM-550FF VM-560FF vScan	VM-810	VM-850
	1.200.03.00011	2" / 50mm Signal Clamp		✓	-	✓	✓	✓
	1.200.15.00001			-	✓	-	-	-
	1.200.03.00012	4" / 100mm Signal Clamp		✓*	-	✓	✓	✓
	1.222.03.00001			✓*	✓	-	-	-
	1.200.03.00004	5" / 125mm Signal Clamp		✓*	-	✓	✓	✓
	1.222.04.00001			✓*	✓	-	-	-
	1.219.09.00001	5" / 125mm SiS Signal Clamp		✓	✓	-	-	-
	1.219.08.00002	9" / 230mm Signal Clamp		✓*	-	✓	✓	✓
	1.219.08.00001			✓*	✓	-	-	-
	1.200.03.00006	18" / 450mm Flexible Signal Clamp		✓	-	✓	✓	-
Clamp and Leads Adapter								
	2.219.02.00094	Adapter, 3 pin silver plug to Twist/Lock plug.		✓	-	✓	✓	✓
Clamp extension rod								
	1.204.08.00001	The extension rod is compatible with all clamps except the 18" flexible.						

 3 Pin Silver Plug

 Twist/Lock plug

* SiS 8.44kHz and 9.82kHz

INTERMOUNTAIN SALES, INC.

Utility Tools for Today!

**3792 South Lipan Street
Englewood, Colorado 80110**

Telephone: (303) 762-1070 or 1-800-373-3212
FAX: (303) 762-0996 www.intermntnsales.com

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free: 1-800-446-3392

Tel: +1-408-734-3880

www.vivax-metrotech.com

Tag us on social media @vivax_metrotech



V1.0

Please visit our website for full product specifications.

www.vivax-metrotech.com | www.vxmt.com